HP DesignJet T1600 Printer series



Designed to deliver – Extraordinary performance to move projects forward



Experience simplicity – At the high-end

- Adopt a smart workstyle with the easiest PDF printing¹ using HP Click software.
- Empower your workforce. Easily print and share jobs from the cloud with your mobile device and HP Smart app.
- Fits your workplace with the most compact footprint and most quiet operation, with up to 87% less noise.2

Unleash performance – To turn design into delivery

- Showcase design versatility from precise line drafts to boldly colored 3D renders, with HP Bright Office Inks.
- Provide the highest accuracy and display the finest details with the unique Adobe PDF Print
- Meet deadlines with the fastest speed up to 180 A1/hr², and dual roll option.4
- Cut out unproductive tasks with integrated automatic print stacking, up to 100 pages.

Secure – World's most secure large-format printer⁵

- Rely on the best network protection with features like HP Secure Boot and whitelisting.5
- Control who accesses the printer and its confidential documents with secure user authentication.
- Keep your fleet secure at any time with HP JetAdvantage Security Manager.

For more information, please visit http://www.hp.com/go/designjett1600

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Compared to Canon Direct Print & Share and based on "One Click Print." Once image is selected, one-click printing when printing the entire file without any modifications to the print settings. Applicable to PDF, JPEG, TIFF,

Based on comparable large-format inkjet printers under €12,000 as of December, 2018. IDC figures show that Canon, Epson, and HP combine for 98% share of this printing category worldwide as of 03, 2018. Fastest print speed based on sustained printing speeds. Most compact footprint calculated using all devices in "Operation mode" with an Open Basket and the arm of the Screen (front panel) spread out to enable user interaction Most quiet according to internal HP testing of sound pressure level during operating mode (plain paper, line drawing, Normal mode) compared to published specification of competitive printers. Percentage calculations of

noise based on lineal units vs. Canon TX-3000 published spec of 51dB(A).

Requires purchase of the HP DesignJet T1600 PostScript® models or optional HP DesignJet PostScript/PDF Upgrade Kit. Highest accuracy and finest details compared to printers without the embedded Adobe technology excluding RIP users, and based on internal HP testing with PDF files containing special fonts, PANTONE® colours, smooth shading, overprint, and transparencies that can only be reproduced using the Adobe PDF Print Engine. The Adobe PDF Print Engine (APPE) is Adobe's high speed, high fidelity print platform. To learn more, visit http://www.adobe.com/products/pdfprintengine.

Dual rolls included with HP DesignJet T1600dr printers only.

⁵ Advanced embedded security features are based on HP review of 2019 published embedded security features of competitive printers, as of February 2019

Technical specifications

Pint speak 180 A / Tr. 19.3 sec/41 Pint resolution Up to 2400 x 1200 optimised dpi Technology Pin Terminal Inlight Redricology Pint Terminal Inlight Redricology Redricology Pint Terminal Inlight Redricology Pint Terminal Inlight Redricology Pint Terminal Inlight Redricology Dyse based (C, NY, Yp. C, Pingmert-based (m/O) Pint speak 1. Livresca (Tr. NY, Yp. C, Pingmert-based (m/O) Pint speak 1. Livresca (Tr. NY, Yp. C, Pingmert-based (m/O) Pint speak 1. Livresca (Tr. NY, Yp. C, Pingmert-based (m/O) Pint speak 1. Livresca (Tr. NY, Yp. C, Pingmert-based (m/O) Pint speak 1. Livresca (Tr. NY, Yp. C, Pingmert-based (m/O) Pint speak 1. Livresca (Tr. NY, Yp. C, Pingmert-based (m/O) Pint speak 1. Livresca (Tr. NY, Yp. C, Pingmert-based (m/O) Pint speak 1. Livresca (Tr. NY, Yp. C, Pingmert-based (m/O) Pint speak 1. Livresca (Tr. NY, Yp. C, Pingmert-based (m/O) Pint speak 2. Livresca (Tr. NY, Yp. C, Pingmert (Tr. Ny, Yp. C	Print	
Rechrology Regiss Refit 3 x 3 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 2 x 3 x 3 mm Select 3 x 3 mm Select 3 x 3 mm Select 3 x 3 x 3 mm Select 3	Print speed	180 A1/hr, 19.3 sec/A1 ¹
Margins Speil 3 x 3 x 3 x 3 x 3 x 3 x 3 x 3 x 3 x 3	Print resolution	Up to 2400 x 1200 optimised dpi
Sheet 3 x 2 x 3 x 3 mm If types Dept-based (M, Y, EK, Gi, Pigneret-based (mK) Printheads 1 universal printhead	Technology	HP Thermal Inkjet
Proteineads	Margins	
Behavior of the accuracy 10.1 %	Ink types	Dye-based (C, M, Y, pK, G); Pigment-based (mK)
Minimum line width 0.02 mm (PDF addressable at 1200 dpl)	Printheads	1 universal printhead
Media Handling Sheet Feed, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, media bin, automatic horizontal cutter	Line accuracy	±0.1% ²
Sheet feed, automatic front-loading roll feed, smart roll switching ³ , integrated output stacker, media bin, automatic front-loading roll feed, smart roll switching ³ , integrated output stacker, media bin, automatic front-loading roll feed, smart roll switching ³ , integrated output stacker, media bin, automatic form routput (automatic cutter)	Minimum line width	0.02 mm (PDF addressable at 1200 dpi)
Bottszer 279 to 914 km m Sheet size 279 to 914 x 1219 mm Sheet size 210 x 279 to 914 x 1219 mm Sheet size 210 x 279 to 914 x 1219 mm Standard sheets A4, A3, A2, A1, A0 Grammage 60 to 328 g/m² Thickness Up to 0.5 mm Applications Line drawings, Maps, Orthophotos, Presentations, Renderings Memory 128 GB (Bite processing) ⁴⁴ Hard disk 500 GB self-encrypting Connectivity Interfaces Gligabit Ethornet (10008psa-T), supporting the following standards: TCD(ID BourDDEACC (ID-4 cmy), DHCP-6, TETD (ID-4 cmy), SMM (n1) x 2x, x3), Anghe Borjoin Compatible, WG Discovery, Embedded Web Server HTTP HTTPS; IP-Sec, SMTP (ermal), Saw IP printing (9100), IP-D, IPP, WS print, NTLM v2, SMB-x, SSLT, Sauthentication (LEAP, PEAR, EAP-TILS), DES Print languages (standard) PostScript Printer: Anobe PostScript 3, Adobe POST, 17, IPI-GLIZ, HP-RTL, TIFF, IPEG, CALS G4 Non-PostScript Printer: ADDE PostScript 3, Adobe POST, 17, IPI-GLIZ, HP-RTL, TIFF, IPEG, CALS G4 Printing pasts Direct printing from LSB (Blash drive, print from reture): shared folder, email printing, HP driver for Windows, HP Print Graver of Anotolo, Apple APPTHIC three for MacOS and for 105, HP Print for Chrome OS, HP Click, HP Smart App for IOS and Androac Apple APPTHIC three for MacOS and for 105, HP Print for Chrome OS, HP Click, HP Smart App for IOS and Androac Apple APPTHIC three for MacOS and for 105, HP Print for Chrome OS, HP Click, HP Smart App for IOS and Androac Apple APPTHIC three for MacOS and for 105, HP Print for Chrome OS, HP Click, HP Smart App for IOS and Androac Apple APPTHIC three for MacOS and for 105, HP Print for Chrome OS, HP Click, HP Smart App for IOS and Androac Apple APPTH (ID-1) (IN-1) (IN	Media	
Sheet size 210 x 279 to 914 x 1219 mm Standard sheets AA, A3, A2, A1, A0 Grammage 610 s 288 Jm² Thickness Up to 0.5 mm Applications Line drawings, Maps, Orthophotos; Presentations; Renderings Memory 128 GB filte processing?* Hard disk 500 GB self-encrypting Connectivity Interfaces Glapbit Ethernet (10008sex-T), supporting the following standards: TCVIVID Booth/DNCP (IPN-4 only), UNCPA, TETP (IPN-4 only), SMM (vi), vox, v3), Apple Borjoin (Compatible, WC Bioscowe), Embedded Wes Server HITTB HITTS), IPSE (SMT) (email), Raw IP printing (9100), IPD, IPP, WS print, NTLM v2, SMB, x3, SST/TLS, 802.1X authentication (LEAP, PEAR, EAP-1TLS), IPSE Print languages (standard) PostScript Printer: Abobe PostScript 3, Adobe PDF 117, IPB-GLZ, IPR-RTL, TIFF, IPSG, GLA SG AND-PostScript Printer: Abobe PostScript 3, Adobe PDF 117, IPB-GLZ, IPR-RTL, TIFF, IPSG, GLA SG AND-PostScript Printer: Abobe PostScript 3, Adobe PDF 117, IPB-GLZ, IPR-RTL, TIFF, IPSG, GLA SG AND-PostScript Printer: Abobe PostScript 3, Adobe PDF 117, IPB-GLZ, IPR-RTL, TIFF, IPSG, GLA SG AND-PostScript Printer: Abobe PostScript 3, Adobe PDF 117, IPB-GLZ, IPR-RTL, TIFF, IPSG, GLA SG AND-PostScript And Andrew PostScript A, Adobe PDF 117, IPB-GLZ, IPR-RTL, TIFF, IPSG, GLA SG AND-PostScript Printer: Abobe PostScript 3, Adobe PDF 117, IPB-GLZ, IPR-RTL, TIFF, IPSG, GLA SG AND-PostScript Printer: Abobe PostScript 3, Adobe PDF 117, IPB-GLZ, IPR-RTL, TIFF, IPSG, GLA SG AND-PostScript Printer: Abobe PostScript 3, Adobe PDF 117, IPB-GLA SG AND AND-PostScript Printer: Abobe PostScript A, Adobe PDF 117, IPB-GLA SG AND AND-PostScript Printer: Abobe PostScript A, Adobe PDF 117, IPB-GLA SG AND	Handling	
Standard sheets AAI, A3, A2, A1, A0 Grammage 60 to 328 g/m² Trischness Up to 0.5 mm Applications Line drawings, Maps; Orthophotos; Presentations, Renderings Memory 128 GB ffile processing!* Hard disk 500 GB self-encrypting Connectivity Interfaces Gligabit Ethernet (1008ase-1), supporting the following standards: TO/IP BootP/DHCP (IPvd only), DHCPv6, TETP (IPvd only), CHCPv6, TETP (IPvd only	Roll size	279 to 914 mm
Grammage 60 to 328 g/m² Thickness Up to 0.5 mm Applications Line dawings: Maps: Orthophotos; Presentations; Renderings Memory 128 Get (file processing) ⁴ Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/GHCP (IPv4 only), DHCPv6, TFTP (IPv4 only), SNMP VII. v2c, V3), Apple Borjour Compatible, W5 Discovery, Ernbedded Web Server (HTTH HTTPS), Pisec, SMTP (IPv4 only), SNMP VII. v2c, V3), Apple Borjour Compatible, W5 Discovery, Ernbedded Web Server (HTTH HTTPS), Pisec, SMTP (IPv4 only), SNMP VII. v2c, V3), Apple Borjour Compatible, W5 Discovery, Ernbedded Web Server (HTTH HTTPS), Pisec, SMTP (IPv4 only), SNMP VII. v2c, V3), Apple Borjour Compatible, W5 Discovery, Ernbedded Web Server (HTTH HTTPS), Pisec, SMTP (IPv4 only), SMMP VII. v2c, V31, Apple Borjour Compatible, W5 Discovery, Ernbedded Web Server (HTTH HTTPS), Pisec, SMTP (IPv4 only), SMMP VII. v3c, V31, Apple Borjour Compatible, W5 Discovery, Ernbedded Web Server (HTTH HTTPS), Pisec, SMTP (IPv4 only), SMMP VII. v3c, V3c, V3c, V3c, V3c, V3c, V3c, V3c, V	Sheet size	210 x 279 to 914 x 1219 mm
Thickness Up to 0.5 mm Applications Line drawings, Maps, Orthophotos; Presentations; Renderings Memory 128 GB file processing ¹⁴ Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BoatP/DHCP (IPv4 only), DHCPv6, TFTP (IPv4 only), SMPP (V), V2c, V3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP HTTPS), IPsec, SMP only), SMPP (V), V2c, V3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP HTTPS), IPsec, SMP only), SMPP (V), V2c, V3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP HTTPS), IPsec, SMP only), SMPP (V), V2c, V3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP HTTPS), IPsec, SMP only), SMPP (V), V2c, V3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP HTTPS), IPsec, SMP only), SMPP (V), V2c, V3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP HTTPS), IPsec, SMP only), SMPP (V), V2c, V3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP HTTPS), IPsec, SMPP (V), V2c, V3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP HTTPS), IPsec, SMPP (V), V2c, V3), Apple Bonjour Compatible, V4c, V4c, V4c, V4c, V4c, V4c, V4c, V4c	Standard sheets	A4, A3, A2, A1, A0
Applications	Grammage	60 to 328 g/m²
Memory 128 GB (file processing) ⁴ Hard disk 500 GB self-encrypting Connectivity Interfaces Glapbit Ethernet (1000Base-17), supporting the following standards: TCP/IP_BootP/DHCP (IPv4 only), DHCPv6, TFTP (IPv4 only), SNAP (VI v.2c, V3), Apple Borjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS, I), Piec, KTP, Cerciting, May Portining (1000), IPV, IPv WS, Discovery, Embedded Web Server (HTTP, HTTPS, II), Piec, KTP, Cerciting, May Portining (1000), IPV, IPv WS, Discovery, Embedded Web Server (HTTP, HTTPS, II), Piec, KTP, TSI, IVP, Cerciting, May Portining (1000), IPV, IPv WS, Discovery, Embedded Web Server (HTTP, HTTPS, II), Piec, KTP, TSI, TSI, Piec, CALS G4 Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/Z, HP-RTL, TIFF, JPEG, CALS G4 Print languages (spitonal) Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple AirPrint driver for MacOs and for IOS, IPP Print for Throme US, HP Click, HP Smart App for IOS and Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Security features HP Secure Book, Whitelisting, TPM, Role Based Access Control, LDAP and Kreberos authentication, SNMPV3, HTTPS, Secure-IPP, Ibp-sec/Frievalid, Certificates management, 802.1X, TS, L10, 11.11, 2, IP Web Jeadmin compatible, IPP Jeadwantage Security Manager compatible, Secure Disk erase (IDoD S220,22-M), Secure File erase, self-encrypting HDD, encrypted PNP printing, Sysiog security logging Dimensions (w x d x h) Printer Single-roll: 313 kg, dual-roll: 85 kg Shipping Single-roll: 313 kg, dual-roll: 85 kg Shipping Single-roll: 313 kg, dual-roll: 85 kg Shipping Single-roll: 313 kg, dual-roll: 85 kg Printer Single-roll: 313 kg, dual-roll: 85 kg Shipping Single-roll: 313 kg, dual-roll: 85 kg Shipping Single-roll: 313 kg, dual-roll: 85 kg Shipping Sin	Thickness	Up to 0.5 mm
Hard disk S00 GB self-encrypting	Applications	Line drawings; Maps; Orthophotos; Presentations; Renderings
Connectivity Interfaces (algabit Ethernet (1000Base-T), supporting the following standards: TCPIPI BootP/DHCP (IPv4 only), DHCPv6, TFTP (IPv4 only), SMMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec, SMTP TLS, DFS Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/Z, HP-RTL, TIFF, IPEG, CALS G4 Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7 Print languages (sptional) Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive print from network shared folder, email printing, HP driver for Windows, HP Print Service for Adroid, Apple Air/Print driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart App for iOS and Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, Air Print for macOS Non-PostScript Printer: Raster drivers for Windows, Air Print for macOS Security features HP Secure Boot, Whitelstring, TPM, Role Based Access Control, LDAP and Keeberos authentication, SNMPv3, HTTPS, Secure-PIP) Pipe-Effreivall, Cettificates management, 802.17, ITS, 1.0/1.171, 2, HP Web Detadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (Dio 5220.22-H)), Secure File erase, self-encrypting HDD, errorypted Film printing, Sysiog security logging Dimensions (wx xd xh) Printer 1390 x 760 x 1080 mm Weight Printer Single-roll: 13 kg, dual-roll: 13 kg, dual-roll: 13 kg, dual-roll: 17 kg What's in the box HP Designier TisoO Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords Security Manager, HP SmartTracker (optional) Environmental ranges Operating Humidity 2 to 8 09% RH Storage temperature 5 to 35%C Dough pressure 42 dB(A) (operating), 32 dB(A) (ide), <17 dB(A) (sleep) Sound power 5 5 9 B(A) (operating), 43 dB(A) (ide), <3.5 B(A) (sleep) Power Consumption 100 W (printing); <36 W (ready); <1 W (<10 W with embedded D	Memory	128 GB (file processing) ⁴
interfaces Gigabit Ethernet (1000Base-7), supporting the following standards: TCP/IP, BootP/DHCP (IPV4 only), DHCPv6, TFTP (IPV4 only), SMMP (v.), Vac., v.3), Apple Bonijour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), Precs, SMTP (ternat), Alexa IP printing (1900), H.D., IPV5, Sprint, NTLM v.2), SMMP (v.), SMMP (v.), Tecs, SMTP (ternat), SMMP (v.), SMMP (v.), Vac., Val., Apple Bonijour (compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), Precs, SMTP (ternat), SMMP (v.), Precs, SMTP (ternat), SMMP (v.), Precs, SMTP (ternat), SMMP (v.), Precs, SMTP, SMMP, SMMP, SMMP, SCI., Vac., SMMP, SM	Hard disk	500 GB self-encrypting
only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), PSec, SMTP (email), Raw IP printing (9100), LPD, IPV WS print, NTML v2, SMBV3, SSL/TLS, 802.1X authentication (LEAR PEAR EAP TLS), DFS Print languages (standard) PSScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4 Non-PostScript Printer: Adobe PostScript 13, Adobe PDF 1.7 Print languages (optional) Non-PostScript Printer: Adobe PostScript 13, Adobe PDF 1.7 Printing paths Direct printing from USE flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple Air Print driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart App for iOS and Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, Air Print for macOS Non-PostScript Printer: Raster drivers for Windows, Air Print for macOS Non-PostScript Printer: Raster drivers for Windows, Air Print for macOS Security features PostScript Printer: Raster drivers for Windows, Air Print for macOS Security features ##P Secure Boot, Wintites Ing. TIPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPV3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD S220.22-M), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 1390 x 760 x 1080 mm Shipping 1477 x 767 x 800 mm Weight Printer Single-roll: 113 kg, dual-roll: 85 kg Shipping Single-roll: 113 kg, dual-roll: 85 kg What's in the box HP DesignJet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords Five Tomage and solutions Five Tomage Tomage Air Printing Air	Connectivity	
Non-PostScript Printer: HP-GI/Z, HP-RTL, TIFF, JPEG, CALS G4 Print languages (optional) Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, JHP driver for Windows, AHP Print Service for Android, Apple AirPrint driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart App for iOS and Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Non-PostScript Printer: Raster drivers for Windows, AirPrint for macOS Security features Posture Box, Whitelisting, TPM, Box leads and screen control, LDAP and Kerberos authentication, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1 N. TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, Pietral-Avantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 1390 x 760 x 1080 mm Shipping 1477 x 767 x 800 mm Weight Printer Single-roll: 82 kg, dual-roll: 85 kg Shipping Single-roll: 113 kg, dual-roll: 85 kg Shipping Single-roll: 113 kg, dual-roll: 117 kg What's in the box HP DesignJet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C Operating temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power <5.9 B(A) (operating), 4.9 B(A) (idle), <3.5 B(A) (sleep) Power Consumption 100 W (printing), <36 W (ready); <1 W (<10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Entification Environ	Interfaces	only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec, SMTP (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP, PEAP, EAP-
Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple AirPrint driver for MacOS and for 105, HP Print for Chrome OS, HP Click, HP Smart App for 10S and Android	Print languages (standard)	
Service for Android, Apple AirPrint driver for MacOS and for iOS, HP Click, HP Smart App for iOS and Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Non-PostScript Printer: Raster drivers for Windows, AirPrint for macOS Security features HP Secure Boty, Mitellating, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPy3, HTTPS, Secure-IPP, IPsec/Firevall, Certificates management, 802.1 X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP Jetadwantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 1390 x 760 x 1080 mm Weight Printer Single-roll: 82 kg, dual-roll: 85 kg Shipping Single-roll: 113 kg, dual-roll: 117 kg What's in the box HP DesignJet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP Smart Tracker (optional) Environmental ranges Operating temperature 5 to 35°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Fower Consumption 100 W (printing); <36 W (ready); <1 W (<10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental Environmental Environmental Environmental Enveronmental Environmental Enveronmental Enveronmental Enveronmental Enveronmental	Print languages (optional)	Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7
Non-PostScript Printer: Raster drivers for Windows, AirPrint for macOS	Printing paths	Service for Android, Apple AirPrint driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart App for iOS
Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, IPP Web Jetadmin compatible, IPP Jetadvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting HDD, encrypted IPN printing, Syslog security logging Dimensions (w x d x h) Printer 1390 x 760 x 1080 mm Shipping 1477 x 767 x 800 mm Weight Printer Single-roll: 82 kg, dual-roll: 85 kg Shipping Single-roll: 113 kg, dual-roll: 117 kg What's in the box HP DesignJet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C Operating temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power	Drivers	PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Non-PostScript Printer: Raster drivers for Windows, AirPrint for macOS
Printer 1390 x 760 x 1080 mm Shipping 1477 x 767 x 800 mm Weight Printer Single-roll: 82 kg, dual-roll: 85 kg Shipping Single-roll: 113 kg, dual-roll: 117 kg What's in the box HP Design Jet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C Operating temperature 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power <5.9 B(A) (operating), 4.9 B(A) (idle), <3.5 B(A) (sleep) Power Consumption 100 W (printing); <36 W (ready); <1 W (<10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), Z A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Security features	Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting HDD,
Shipping 1477 x 767 x 800 mm Weight Printer Single-roll: 82 kg, dual-roll: 85 kg Shipping Single-roll: 113 kg, dual-roll: 117 kg What's in the box HP Design Jet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C Operating temperature 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power <5.9 B(A) (operating), 4.9 B(A) (idle), <3.5 B(A) (sleep) Power Consumption 100 W (printing); <36 W (ready); <1 W (<10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Dimensions (w x d x h)	
Weight Printer Single-roll: 82 kg, dual-roll: 85 kg Shipping Single-roll: 113 kg, dual-roll: 117 kg What's in the box HP DesignJet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C Operating temperature 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep)	Printer	1390 x 760 x 1080 mm
Weight Printer Single-roll: 82 kg, dual-roll: 85 kg Shipping Single-roll: 113 kg, dual-roll: 117 kg What's in the box HP Designalet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power <5.9 B(A) (operating), 4.9 B(A) (idle), <3.5 B(A) (sleep) Power Consumption 100 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Shipping	
Printer Single-roll: 82 kg, dual-roll: 85 kg Shipping Single-roll: 113 kg, dual-roll: 117 kg What's in the box HP DesignJet T1600 Printer, printer stand and media bin, spindle(s) ¹⁵ , printheads, introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power <5.9 B(A) (operating), 4.9 B(A) (idle), <3.5 B(A) (sleep) Power Consumption 100 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT		
Shipping Single-roll: 113 kg, dual-roll: 117 kg What's in the box HP DesignJet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C Operating temperature 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power ≤5.9 B(A) (operating), 4.9 B(A) (idle), ≤3.5 B(A) (sleep) Power Consumption 100 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT		Single-roll: 82 kg. dual-roll: 85 kg
What's in the box HP Design Jet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) Environmental ranges Deparating temperature 5 to 35°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power ≤5.9 B(A) (operating), 4.9 B(A) (idle), ≤3.5 B(A) (sleep) Power Consumption 100 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT		
Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power <5.9 B(A) (operating), 4.9 B(A) (idle), <3.5 B(A) (sleep) Power Consumption 100 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT		HP DesignJet T1600 Printer, printer stand and media bin, spindle(s) ⁵ , printheads, introductory ink cartridges, user guide,
Operating temperature 5 to 35°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power ≤5.9 B(A) (operating), 4.9 B(A) (idle), ≤3.5 B(A) (sleep) Power Consumption 100 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	HP Software and solutions	
Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power <5.9 B(A) (operating), 4.9 B(A) (idle), <3.5 B(A) (sleep) Power Consumption 100 W (printing); <36 W (ready); <1 W (<10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Environmental ranges	
Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power \$5.9 B(A) (operating), 4.9 B(A) (idle), \$3.5 B(A) (sleep) Power Consumption 100 W (printing); < 36 W (ready); < 1 W (<10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Operating temperature	5 to 35°C
Acoustics Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power \$5.9 B(A) (operating), 4.9 B(A) (idle), <3.5 B(A) (sleep) Power Consumption 100 W (printing); < 36 W (ready); < 1 W (<10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Operating humidity	20 to 80% RH
Sound pressure 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) Sound power \$5.9 B(A) (operating), 4.9 B(A) (idle), \$3.5 B(A) (sleep) Power Consumption 100 W (printing); <36 W (ready); <1 W (<10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Storage temperature	-25 to 55 ^o C
Sound power \$5.9 B(A) (operating), 4.9 B(A) (idle), \$3.5 B(A) (sleep) Power Consumption 100 W (printing); \$3.6 W (ready); \$1 W (\$10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (\$10%), \$50/60 Hz (\$3 Hz), \$2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Acoustics	
Power Consumption 100 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Sound pressure	42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep)
Consumption 100 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Sound power	≤5.9 B(A) (operating), 4.9 B(A) (idle), ≤3.5 B(A) (sleep)
Consumption 100 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	Power	
Certification Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, RoHS (EU), REACH, EPEAT	Consumption	100 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)
Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, RoHS (EU), REACH, EPEAT	Requirements	Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max
Safety EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, RoHS (EU), REACH, EPEAT	Certification	
Electromagnetic Compliant with Class B requirements, including: EU (EMC Directive) Environmental ENERGY STAR, ErP, WEEE, RoHS (EU), REACH, EPEAT		EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA)
Environmental ENERGY STAR, ErP, WEEE, RoHS (EU), REACH, EPEAT		

Ordering information

3EK10A 3EK11A 3EK12A 3EK13A	HP DesignJet T1600 36-in Printer HP DesignJet T1600 36-in PostScript Printer HP DesignJet T1600dr 36-in Printer HP DesignJet T1600dr 36-in PostScript Printer
Accessories	
5NB95A	HP SmartTracker USB for DesignJet
5NB95AAE	HP SmartTracker for DesignJet
CN538A	HP DesignJet 3-in Core Adapter
G6H50B	HP SD Pro 44-in Scanner
G6H51B	HP HD Pro 42-in Scanner
Ν7Ρ/17ΔΔ	HP LISB 3.0 to Gigabit LAN Adapter

Original HP printing supplies

1XB25A	HP 730F 300-ml Yellow DesignJet Ink Cartridge
1XB26A	HP 730F 300-ml Magenta DesignJet Ink Cartridge
1XB27A	HP 730F 300-ml Cyan DesignJet Ink Cartridge
1XB28A	HP 730F 300-ml Photo Black DesignJet Ink Cartridge
1XB29A	HP 730F 300-ml Gray DesignJet Ink Cartridge
1XB30A	HP 730F 300-ml Matte Black DesignJet Ink Cartridge
DODOEV	UD 727 Docide lot Drinthood

Dispoyar Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, wist hp.com/go/OriginalHPinks.

Original HP large format printing materials

C6810A HP Bright White Inkiet Paper (FSC® certified)⁶ (recyclable)⁷ 914 mm x 91.4 m (36 in x

300 tt)
C6980A HP Coated Paper (PEFC™ certified)⁶ (recyclable)⁷ 914 mm x 91.4 m (36 in x 300 ft)
LSC80A HP Universal Heavyweight Coated Paper, 3-in Core (FSC® certified)⁶ (recyclable)⁷ 914
mm x 91.4 m (36 in x 300 ft)
D9R28A HP Everyday Matte Polypropylene, 3-in Core 914 mm x 61 m (36 in x 200 ft)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

UB8P0E (1-roll)/UB8T2E (2-roll) HP 3 year Next Business Day Onsite Hardware Support with

Defective Media Retention
UB8P1E (1-roll)/UB8T3E (2-roll) HP 4 year Next Business Day Onsite Hardware Support with

UBBP1E (1-roll)/UBB1 3E (2-roll) HP 4 year Next Business Day Unsite Hardware Support with Defective Media Retention UBBP2E (1-roll)/UBBT4E (2-roll) HP 5 year Next Business Day Onsite Hardware Support with Defective Media Retention UBBP3PE (1-roll)/UBBT5PE (2-roll) HP 1 year Post Warranty Next Business Day Onsite Hardware Support with Defective Media Retention UTXV4E HP Preventive Maintenance Service H451BE HP Installation Service with Network Setup

HP DesignJet Support Services offer installation, maintenance, and extended support services (e.g. 2,3, 4 and 5 years). For more information, please visit hp.com/go/cpc

ECO highlights

- Save paper with automatic print settings and image nesting ENERGY STAR® certified¹ and EPEAT® registered² Free, convenient HP ink cartridge recycling³ FSC®-certified papers⁴, recyclable HP media; some HP media eligible for take-back

Please recycle large-format printing hardware and printing supplies. Find out how at our website: http://www.hp.com/ecosolutions

1 ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.
2 EPEAT "registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
3 Program availability varies. Please check http://www.hp.com/recycle for details.
4 BMG trademark license code FSC*-C113719, see http://www.hs.corg. HP trademark license code FSC*-C101734, see http://www.hsc.org. HP trademark license code FSC*-C101734, see http://www.hsc.org. materials, please visit http://www.HPLFMedia.com.
5 Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.















¹ Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks.
² ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on AO/E HP Matte Film in Best or Normal mode with Original HP inks
³ Applicable for dual-roll printers only.
⁴ Based on 4 GB RAM.
⁵ Single-roll printers come with one spindle, dual-roll printers come with two spindles.