

Product datasheet

Specifications



APC Smart-UPS Lithium Ion, Short Depth 750VA, 230V with SmartConnect

SMTL750RM12UC

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead Time Usually in Stock

Main

Main Input Voltage 230 V

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated Power In W 600 W

Rated Power In Va 750 VA

Input Connection Type IEC 60320 C14

Output Connection Type 6 IEC 60320 C13
2 IEC Jumpers

Number Of Rack Unit 2U

Battery Type Li-Ion (Lithium-Ion)

Provided Equipment USB cable
Ethernet patch cable
Rack mounting brackets
Screw
Washer
Rack mounting support rails

Complementary

Software Package SmartConnect software for remote power monitoring feature availability varies by terms of use

Batteries & Runtime

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Battery Graph Comments This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v

Extended Runtime 0

Battery Recharge Time	3 h
Battery Design Life	8...10 year(s)
Battery Charger Power	50 W rated

General

Product Web Sub-Family	Cloud-enabled monitoring
Redundant	No

Physical

Colour	Black with silver front bezel
Height	8.6 cm
Width	43.8 cm
Depth	31.8 cm
Net Weight	15.4 kg
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Usb Compatible	Yes

Input

Input Protection Type	Circuit breaker
Input Voltage Limits	151...302 V adjustable 160...286 V
Network Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Crest Factor	3 : 1
Harmonic Distortion	Less than 5 %
Maximum Configurable Power In Va	750 VA
Maximum Configurable Power In W	600 W
Transfer Time	6 ms typical : 10 ms maximum
Ups Type	Line interactive
Wave Type	Sine wave
Output Frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	C-Tick CE EAC
Standards	EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic Level	41 dBA
Heat Dissipation	135 Btu/h

Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...7620.00 m
Ip Degree Of Protection	IP20
Relative Humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing

Communications & Management

Alarm	Audible and visible alarms
Control Panel	Multifunction LCD status and control console
Free Slots	1
Communication Port Support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge Energy Rate	645 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	22.9 cm
Package 1 Width	47.2 cm
Package 1 Length	58.4 cm
Package 1 Weight	18.6 kg

Contractual warranty

Warranty	5 year repair or replace
-----------------	--------------------------

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.


[Learn more about Green Premium >](#)



Transparency RoHS/REACH

Well-being performance

 Mercury Free

 RoHS Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)